

S/FTP Cat.7 Copper Patch Cord

EN 50173-1, EN 50288-4-2, ISO/IEC 11801, IEC 61156-6

Complaint Standards

EIA/TIA-568-C.2, ISO/IEC 11801 2nd ed, IEC 61156-5, EN 50173-1, EN 50288-6-1,

Applications

IEEE 802.3: 10Base-T;100Base-T;1000Base-T

IEEE 802.5 16 MB; ISDN;TPDDI;ATM

Power over Ethernet (PoE) / Type 1-4

Flame Resistance for Cable

EN 50399: Class Eca

LSHF(LSOH): IEC 60332-1; IEC 60754-2; IEC 61034

Features

100% performance tested by Viavi 40G Certifier to guarantee the quality

Small diameter, Flexible cable for easy routing

Snagless boots to prevent latch damage

Assembly Wiring Standard T568B

(T568A or Cross-over can be requested)



Assembly Order Coding

RJ45M-RJ45M-C07-SFTP-FLX-OG-XXM

Sample Code

RJ45M-RJ45M-C07-SFTP-FLX-OG-05M

Available Jacket Colors

Blue, Grey, Red, Green, Orange

Construction

Conductor	Stranded bare copper wire Ø 0.42 mm AWG 27/7
Side A/B Connector Type	RJ45 Male / RJ45 Male
Sheath	Foam skin polypropylen, Ø 0.98 mm nom LSHF-FR
Contact pin material	Phosphor-bronze alloy coated with 50 µ of gold
Outer cable diameter	5.9 mm
Color (standard)	Cable; orange RAL 7035 Boots; black RAL 9005

Mechanical Properties

Insertion / extraction cycles	min. 500
Temperature range	during operation -20°C up to + 60°C
	during installation 0°C up to + 50°C
Min. bending radius	Installation 25 mm
	Installed 50 mm