

U/UTP Cat.6 Copper Patch Cord

Category 6 patch cord is a standardized twisted pair cable for Ethernet application, and its standard specifies performance of up to 250 MHz.

Complaint Standards

EIA/TIA-568-C.2, ISO/IEC 11801 2nd ed, IEC 61156-5, EN 50173-1, EN 50288-6-1, IEEE 802.3af/at /bt.

Applications

IEEE 802.3: 10Base-T;100Base-T;1000Base-T
 IEEE 802.5 16 MB; ISDN;TPDDI;ATM
 Power over Ethernet (PoE) / Type 1-4

Flame Resistance for Cable

EN 50399: Class Dcas2d2a1; Class Eca
 LSHF Dca (FRNC): IEC 60332-1; 60754-2; IEC 61034

Features


100% performance tested by Viavi 40G Certifier to guarantee the quality
 Small diameter, Flexible cable for easy routing
 Snagless boots to prevent latch damage
 Assembly Wiring Standard T568B
 (T568A or Cross-over can be requested)

Construction

Conductor	Bare copper wire: Nom. 0.54 AWG 23/24
Side A/B Connector Type	RJ45 Male / RJ45 Male
Sheath	Polyethylene, Ø 0.95 mm nom LSHF-FR
Contact pin material	Phosphor-bronze alloy coated with 50 µ of gold
Outer cable diameter	5,4 mm
Color (standard)	Cable; blue RAL 5012 Boots; black RAL 9005

Mechanical Properties

Insertion / extraction cycles	min. 500
Temperature range	during operation -20°C up to + 60°C
	during installation 0°C up to + 50°C
Min. bending radius	Installation 4 x Diameter
	Installed 8 x Diameter



Assembly Order Coding

RJ45M-RJ45M-C06-UUTP-SLD-BU-XXM

Sample Code

RJ45M-RJ45M-C06-UUTP-SLD-BU-05M

Available Jacket Colors

Blue