



Konektör Tipi (Connector type)	LC	SC	FCPC	ST
Uyumluluk (compliance)	IEC 61754-20 TIA 604-10-A	IEC 61754-4 TIA 604-3	IEC 61754-13 TIA 604-4-A	IEC 61754-2 TIA 604-2
Merkezeleme (Tuning)				
Açısı (in steps)	45°	60°	∞ (APC 60°)	-
Mekanik Performans				
Gerilme kuvveti (tensile load [N])	100	100	100	100
Bükme Testi (Mating durab.)	1000	1000	1000	1000
Çalışma Sıcaklığı (Op. Temp.)	-40° to +85 °C	-40° to +85 °C	-40° to +85 °C	-40° to +85 °C
Alev Alma (Flammability)				
UL 94-V0	•	•	-	-
Renk (Colour of housing)				
SM PC	Mavi (Blue)	Mavi (Blue)	-	-
SM APC	Yeşil (Green)	Yeşil (Green)	-	-
MM	Bej (Beige)	Bej (Beige)	-	-
brass nickel-plated	-	-	•	•
Fiber Tipi				
E9/125	•	•	•	-
G50/125/OM3	•	•	•	•
G62.5/125	•	•	•	•
HCS200/230	-	•	•	-
Diğer Özellikler (Features)				
Tek parça (one piece design)	•	•	•	•
korunmalı (automatic metal shutter)	-	-	-	-
SFF	•	-	-	-
Renk kodu (colour coding)	•	•	-	-
Yüksek kazanım (HighPower)	•	•	-	-
Kablo çapı (cable diameter) [mm]	0.6 - 2.8	0.6 - 3.5	0.6 - 3.5	0.6 - 3.5
Geçiş kaybı (Insertion loss) [dB]				
multimode ≤	0.2	0.2	0.2	0.2
97 % ≤	0.5	0.5	0.5	0.5
SM 0.1dB typ. ≤	0.06	0.06	0.06	-
97 % ≤	0.15	0.15	0.15	-
SM High-End typ. ≤	0.12	0.12	0.12	-
97 % ≤	0.25	0.25	0.25	-
SM LAN-Eco typ. ≤	0.25	0.25	0.25	0.25
97 % ≤	0.7	0.7	0.7	0.7
Dönüş Kaybı (Return loss) [dB]				
singlemode PC >	45	45	45	45
UPC >	50	50	50	-
APC >	85	85	85	-



