

4F Fiber Optic Indoor Termination Box

4 Fiber Splice Capacity, 2 Patch Ports

ITB-10583-2SC-4S-3P is a compact fiber terminal for use at the final fiber termination point in the customer premises.

The ITB-10583-2SC-4S-3P provides mechanical protection and managed fiber control in an attractive format suitable for use inside customer premises.

A variety of possible fiber termination techniques are accommodated.

Features

- Ergonomically & compact design
- Ability to allow cables to enter from rear or bottom of the unit
- Removable cover for easy access
- Indoor use for small and large business premises
- Easy re-entry with a minimum of tools, time and cost
- Up to 4 cores (heat shrink) or 2 cores (3M mechanical splices)
- Can hold 2 SC simplex adaptor or 2 LC duplex adaptor
- Can be used for Blown Tube cable or common cables
- ROHS compliance

Specifications

Model No.	ITB-10583-2SC-4S-3P
	4 Splice Capacity, 2 SC Adaptors, 3 Drop Ports
Model No.	ITB-10583-4LC-4S-3P
	4 Splice Capacity, 4 LC Adaptors, 3 Drop Ports
Spliced Fiber Capacity	4 splices
Size H x L x W	105mm x 83mm x 24mm
Cable Ports	2 patch ports, 3 round ports (10mm)

