

## 24F Fiber Optic Outdoor Termination Box

1 Tray, 1x24 Fibers

### Features

- May be used for cut, uncut and taut sheath applications.
- May be used for all fiber optic cable.
- Sheath retention & central strength member fasten system included.
- Ribbed closure construction and lightweight plastic provides strength and resistance to chemical and U.V attack
- Installation and reentry with a minimum of tools
- Re-enterable and reusable
- All hardware are included
- Protection class: IP65
- RoHS compliance

### Components

- Cover
- Seal gasket
- Splice Tray
- Cable fixing device
- Nylon tie
- Buffer Tube
- Bottom
- Clamp
- Heat shrink sleeves
- Grounding wire
- Labeling paper
- Installation tape

### Optional Accessories

- Duct mounting kits
- Pole mounting kits
- Pressure valve
- Grounding device



Main Port   Drop Ports   Main Port

### Specifications

Model No.	OTB-362217-16P-24-1T-16	
Size (L x W x H)	362mm x 217mm x 107mm	
Spliced Fiber Capacity	24 splices (1 tray x 24)	
Adapter	16 flangeless SC SX/ LC DX adapters / 1x4, 1x8, 1x16 PLC splitter	
Cable Ports (Cable Diameter)	Main ports	4 x 12mm
	Drop ports	16 x 5mm