

288F Fiber Optic Splice Closures

Single Circuit Max: 48 Trays, 48x12 Fibers



Features

- Modular capacity up to 288 fibers
- May be used for cut, uncut and taut sheath applications.
- May be used for all fiber optic cable.

Sheath retention & central strength member fasten system

included.

Closure construction and lightweight plastic provides

- strength and resistance to chemical and U.V attack
- Installation and reentry with a minimum of tools
- All hardware are included
- Protection class: IP68
- RoHS compliance





Application

Underground, Aerial, Vault, Pole Mounting and Wall Mountable











Specifications

Model No.

Model No.

Spliced Fiber Storage Capacity Size | Height x Diameter

Cable Ports

YT01057 | SSC-361250-6P-288-12T/12T-T059A

576x265m, 576 Fibers Capacity, 48 Trays, 6 Port, Enclosure, w/o Mounting Kits

YT01058 | SSC-361250-6P-144-6T/12T-T059A

576x265m, 288 Fibers Capacity, 24 Trays, 6 Port, Enclosure, w/o Mounting Kits

288 splices (12x24)

361mm x 250mm (w/o clamp), 361mm x 300mm (w/ clamp)

1 oval port (30mm), 6 round ports (30mm)

Mounting Kits

See Other Documen

Wall Mounting Kit - 2

Pole Mounting Kit - 2